



Heavy Industrial Spring Retractable Reels

Series 7000 - 10, 13 & 19mm I.D.

The Series 7000 base and guide arms are formed from high-grade steel and engineered with structural forms and gussets to yield the greatest amount of strength. The Series 7000 reels incorporate all steel construction and a baked-on powder coat finish to produce a rugged corrosion resistant product suitable for a wide variety of heavy duty applications.



7850 OLP118

Model w/ Hose	Pressure w/ Hose	Model w/o Hose	Pressure w/o Hose	Hose I.D.		Hose Length		(M)NPTF Hose Outlet	(F)NPTF Reel Inlet	Dimensions (mm)			Shipping Weight
	bar		bar	mm	in	mtr	ft	in	in	Length	Width	Height	kg*
Low Pressure Air/Water Reels Maximum Temperature 65 °C													
7650 OLP118	21	7600 OLP118	35	10	3/8	15	50	1/4	1/2	483	146	514	20
7670 OLP118	21	7600 OLP118	35	10	3/8	21	70	1/4	1/2	483	146	514	21
7850 OLP118	21	7800 OLP118	35	13	1/2	15	50	3/8	1/2	483	146	514	21
7925 OLP118	17	7900 OLP118	35	19	3/4	8	25	3/4 BSPT	3/4 BSPT	483	146	514	21
Medium Pressure Oil Reels Maximum Temperature 99 °C													
		7600 OMP55-118	224	10	3/8	18	60		3/8	483	146	514	19
7850 OMP118	224	7800 OMP118	224	13	1/2	15	50	1/2	1/2	483	146	514	26
High Pressure Grease Reels Maximum Temperature 99 °C													
7650 OHP118	331	7600 OHP118	345	10	3/8	15	50	1/4	1/2	483	257	514	27

Mounts to floor, wall, ceiling or truck. *Weight of model with hose.

Heavy Industrial Dual Pedestal Reels

Series DP7000 / 80000 - 6, 10, 13 & 19mm I.D.

Reelcraft's new Series DP7000 features our patented interlocking base design, which makes the base assembly especially strong and resistant to vibration. Independent testing has proven these reels to stand up to heavy vibration, making them ideal for truck mounted applications. The base and guide arm on all dual pedestal reels is structurally reinforced.



DP7850 OLP118

82100 OLP118

Model w/ Hose	Pressure w/ Hose	Model w/o Hose	Pressure w/o Hose	Hose I.D.		Hose Length		(M)NPTF Hose Outlet	(F)NPTF Reel Inlet	Dimensions (mm)			Shipping Weight
	bar		bar	mm	in	mtr	ft	in	in	Length	Width	Height	kg*
Low Pressure Air/Water Reels Maximum Temperature 65 °C													
DP7450 OLP118	21	DP7400 OLP118	35	6	1/4	15	50	1/4	1/2	419	203	432	21
DP7650 OLP118	21	DP7600 OLP118	35	10	3/8	15	50	1/4	1/2	419	203	432	23
81100 OLP118	21	81000 OLP118	35	10	3/8	30	100	3/8	1/2	610	257	645	37
DP7850 OLP118	21	DP7800 OLP118	35	13	1/2	15	50	3/8	1/2	419	229	432	24
82075 OLP118	21	82000 OLP118	35	13	1/2	22	75	1/2	1/2	610	257	645	39
82100 OLP118	21	82000 OLP118	35	13	1/2	30	100	1/2	1/2	610	257	645	43
83050 OLP118	17	83000 OLP118	35	19	3/4	15	50	3/4 BSPT	3/4 BSPT	610	257	645	40
D83075 OLP118	17	D83000 OLP118	35	19	3/4	22	75	3/4 BSPT	3/4 BSPT	610	362	645	46
D84050 OLP118	17	D84000 OLP118	35	25	1	15	50	3/4 BSPT	1 BSPT	610	387	645	47
Medium Pressure Oil Reels Maximum Temperature 99 °C													
DP7650 OMP118	179	DP7600 OMP118	224	10	3/8	15	50	3/8	1/2	419	203	432	25
DP7850 OMP118	224	DP7800 OMP118	224	13	1/2	15	50	1/2	1/2	419	229	432	29
82075 OMP118	138	82000 OMP118	138	13	1/2	22	75	1/2	1/2	610	257	645	46
83050 OMP118	86	83000 OMP118	104	19	3/4	15	50	3/4 BSPT	3/4 BSPT	610	257	645	44
High Pressure Grease Reels Maximum Temperature 99 °C													
DP7450 OHP118	345	DP7400 OHP118	345	6	1/4	15	50	1/4	1/2	419	203	432	27
DP7650 OHP118	331	DP7600 OHP118	345	10	3/8	15	50	1/4	1/2	419	203	432	29
81075 OHP118	331	81000 OHP118	345	10	3/8	22	75	3/8	1/2	610	257	645	50
81100 OHP118	331	81000 OHP118	345	10	3/8	30	100	3/8	1/2	610	146	645	58

*Weight of model with hose.

Accessories

Reels ordered with hose and bumper are assembled complete and ready to install. Order bumpers separately for reels without hoses. Additional questions? Please visit our website or call for assistance. For more than 40 years, our specialty is offering hose handling solutions.



Hose Bumper
2-HR1004-3



Air & Water Hose Assembly
601022-50

Models listed with an icon are planned stock and should be able to ship same day or next day.