

# Additel 875 Series Dry Well Calibrators




- Three models ranging from  $-40^{\circ}\text{C}$  to  $660^{\circ}\text{C}$
- Portable, rugged, and quick to temperature
- Metrology-level performance in stability, uniformity, accuracy and loading effect
- Dual-zone control
- Process calibrator option provides a multi-channel readout for a reference thermometer, RTDs and TCs, task documentation, and HART communication
- Color touch screen display
- Choose your own range option

## OVERVIEW

If you are serious about portable temperature calibration tools, then you know a good dry-well calibrator is more than just a stable heat source. The Additel 875 Series Dry Well Calibrators combine excellent performance in stability, radial and axial uniformity, and loading with speed, ruggedness and portability. But we don't stop there! The Process Calibrator option adds the capabilities of a three-channel thermometer readout and a loop calibrator. We've also incorporated a unique option to select your own temperature range within the range of the model selected. We're calling this the CYOR option or Choose Your Own Range option. When you purchase the CYOR option, you pick the upper and lower temperature range needed and we calibrate and optimize the dry well's performance over your selected range. Each unit has a color touch screen display, dual-zone control, and much more. You are just going to love these new dry wells!

## FEATURES

Specification	Display
Task	
mA Measurement	
V Measurement	
Stability Indicator	
Connection Instruction	



Specification	Display	Application
<p>PRT Test (External Reference)</p>		
<p>RTD Test</p>		
<p>TC Test</p>		
<p>Transmitter Test</p>		
<p>Switch Test</p>		

## SPECIFICATIONS

### Base Unit Dry Well Specifications

Specification	875-155	875-350	875-660
Temperature Range at 23°C	-40°C to 155°C	33°C to 350°C	33°C to 660°C
Temperature Range by Mode at 23°C	Standard: -30°C to 155°C	N/A	N/A
	Low Temp: -40°C to 155°C		
Display Accuracy	± 0.18°C at Full Range	± 0.2°C at Full Range	± 0.3°C at 33°C
			± 0.3°C at 420°C
			± 0.5°C at 660°C
Stability (30 min)	± 0.01°C at Full Range	± 0.02°C at Full Range	± 0.02°C at 33°C
			± 0.03°C at 50°C
			± 0.04°C at 420°C
			± 0.04°C at 660°C
Axial Uniformity at 60 mm (2.4 in)	Standard: ± 0.05°C at Full Range	± 0.04°C at 33°C	± 0.05°C at 33°C
		± 0.1°C at 200°C	± 0.3°C at 420°C
	Low Temp: ± 0.07°C at Full Range	± 0.2°C at 350°C	± 0.5°C at 660°C
Radial Uniformity	± 0.01°C at Full Range	± 0.01°C at 33°C	± 0.02°C at 33°C
		± 0.015°C at 200°C	± 0.05°C at 420°C
		± 0.02°C at 350°C	± 0.1°C at 460°C
Loading Effect	Standard:	0.08°C (Display Sensor)	0.15°C (Display Sensor)
		0.01°C (External Sensor)	
	Low Temp:	0.1°C (Display Sensor)	0.015°C (External Sensor)
		0.02°C (External Sensor)	
Hysteresis (Display Sensor)	0.025°C	0.03°C	0.1°C
Environmental Conditions	8°C to 38°C guaranteed accuracy		
	0°C to 50°C, 0% to 90% RH non-condensing, 3000 M altitude for normal operation		
Storage Conditions	-20°C to 60°C		
IP Rating	IP20		
Immersion Depth	150 mm (5.9 in)		
Insert OD	25.8 mm (1.02 in)	24.8 mm (0.98 in)	
Heating Time	12 min: -30°C to 155°C (13 min: -40°C to 155°C)	5 min: 33°C to 350°C	15 min: 33°C to 660°C
	4 min: -30°C to 23°C (5 min: -40°C to 23°C)		
	8 min: 23°C to 155°C		
Cooling Time	18 min: 155°C to -30°C (28 min: 155°C to -40°C)	15 min: 350°C to 100°C	23 min: 660°C to 100°C
	8 min: 155°C to 23°C	10 min: 100°C to 50°C	12 min: 100°C to 50°C
	10 min: 23°C to -30°C (20 min: 23°C to -40°C)	10 min: 50°C to 33°C	12 min: 50°C to 33°C
Typical Time to Stability	10 min		
Resolution	0.01°C		
Units	°C, °F, and K		
Display	6.5 in (165 mm) color touch screen		
Size (H x W x D)	320 x 170 x 330 mm (12.6 x 6.7 x 13.0 in)		
Weight	9.9 kg (21.8 lbs)	8.2 kg (18.1 lbs)	
Power Requirements	90-254 VAC, 45-65 Hz, 580 W	90-254 VAC, 45-65 Hz, 1200 W	
Mechanical Testing	Vibration: 2 g (10-500 Hz), 30 min for 2 sides		
	Impact: 4 g three times		
	Drop test: 500 mm (19.6 in)		
Communication	USB A, USB B, RJ45, WiFi, Bluetooth		
Localization	English, Chinese, Japanese, Russian, German, French, Italian, and Spanish		

## Input Specifications (Process Calibrator [PC] Option)

Specification	Description
Readout Accuracy for 100 ohm PRT (Probe Accuracy Not Included)	$\pm 0.009^{\circ}\text{C}$ at $-40^{\circ}\text{C}$
	$\pm 0.010^{\circ}\text{C}$ at $0^{\circ}\text{C}$
	$\pm 0.012^{\circ}\text{C}$ at $50^{\circ}\text{C}$
	$\pm 0.017^{\circ}\text{C}$ at $155^{\circ}\text{C}$
	$\pm 0.019^{\circ}\text{C}$ at $200^{\circ}\text{C}$
	$\pm 0.026^{\circ}\text{C}$ at $350^{\circ}\text{C}$
	$\pm 0.030^{\circ}\text{C}$ at $420^{\circ}\text{C}$
	$\pm 0.042^{\circ}\text{C}$ at $660^{\circ}\text{C}$
Readout Resolution	1 m $\Omega$
Reference Resistance Range	0 $\Omega$ to 400 $\Omega$
Reference Resistance Accuracy	0 $\Omega$ to 50 $\Omega$ : 0.002 $\Omega$
	50 $\Omega$ to 400 $\Omega$ : 0.004% RD
Reference Characterizations	ITS-90, CVD, IEC-751, Resistance
Reference Measurement Capability	4-wire PRT
Reference Probe Connection	6-pin lemo smart connector
RTD Channels	2
RTD Measurement Accuracy (excl sensor) Compliance	0 $\Omega$ to 25 $\Omega$ : 0.002 $\Omega$
	25 $\Omega$ to 400 $\Omega$ : 0.008% RD
	400 $\Omega$ to 4K $\Omega$ : 0.004% RD
RTD Measurement Resolution	0 $\Omega$ to 400 $\Omega$ : 1 m $\Omega$
	400 $\Omega$ to 4K $\Omega$ : 0.01 $\Omega$
RTD Measurement Resistance Range	0 $\Omega$ to 4K $\Omega$
RTD Characterizations	PT10, PT25, PT50, PT100, PT200, PT500, PT1000, CU10, CU50, CU100, NI100, NI120
RTD Connection	Four 4 mm input jacks
RTD Channels	2 channels. Both accept 2, 3, or 4-wire RTDs
TC Channel	2
TC Measurement Channels	Mini TC terminals: Accepting S, R, K, B, N, E, J, T, C, D, G, L, and U
TC Measurement Accuracy (excl sensor)	Type K: $\pm 0.13^{\circ}\text{C}$ at $0^{\circ}\text{C}$
	$\pm 0.15^{\circ}\text{C}$ at $155^{\circ}\text{C}$
	$\pm 0.18^{\circ}\text{C}$ at $350^{\circ}\text{C}$
	$\pm 0.24^{\circ}\text{C}$ at $660^{\circ}\text{C}$
TC Range	-100 mV to 100 mV
TC Resolution	0.001 V, Input Impedance <1 M $\Omega$
TC Measurement Accuracy (excl sensor)	0 $\Omega$ to 400 $\Omega$ : 1 m $\Omega$ 0 $\Omega$ to 400 $\Omega$ : 1 m $\Omega$
TC Voltage Accuracy	0.02% RD + 5 $\mu\text{V}$
Internal CJC Accuracy	$\pm 0.35$ (ambient from $0^{\circ}\text{C}$ to $50^{\circ}\text{C}$ )
Current Range	-30 mA to 30 mA
Current Accuracy	0.02% RD + 2 $\mu\text{A}$
Current Resolution	0.001 mA, Input Impedance: < 10 $\Omega$




Specification	Description
Voltage Range	-30 V to 30 V
Voltage Accuracy	$\pm 0.02\%$ RD + 2 mV
Voltage Resolution	0.001V; Input impedance: < 1M $\Omega$
Switch Test	Mechanical or Electrical
DC 24V Output	24 V $\pm 1$ V, MAX60 mA
Hart Communication	Optional (ADT875PC Model)
Documentation	Up to 1,000 tasks which store up to 10 results each containing as found and as left data
Temperature Coefficient 0 $^{\circ}\text{C}$ to 8 $^{\circ}\text{C}$ and 38 $^{\circ}\text{C}$ to 50 $^{\circ}\text{C}$	Low temperature heat source: $\pm 0.005^{\circ}\text{C}/^{\circ}\text{C}$
	High temperature heat source: $\pm 0.01^{\circ}\text{C}/^{\circ}\text{C}$
	Ref Readout: $\pm 1$ ppm FS/ $^{\circ}\text{C}$
	RTD Readouts: $\pm 2$ ppm FS/ $^{\circ}\text{C}$
	TC Readouts: $\pm 5$ ppm FS/ $^{\circ}\text{C}$
	Current: $\pm 10$ ppm FS/ $^{\circ}\text{C}$
Voltage: $\pm 10$ ppm FS/ $^{\circ}\text{C}$	



## Ordering Information

### Model Number



### Accessories

Standard Accessories		
Model	Quantity	Picture
Dry well and selected insert	1 pc.	
Power adapter	1 pc.	
USB Cable	1 pc.	
Insert removal tool	1 pc.	
Thermal Shield (ADT875/PC-350/660 only)	1 pc.	
Silica gel plug (ADT875/PC-155 only)	1 set (3 pcs.)	
Insulation plug (ADT875/PC-155 only)	1 set (3 pcs.)	
Test leads (ADT875PC only)	2 set (6 pcs.)	
Certificate of calibration	1 pc.	
CD Manual	1 pc.	

### Optional Accessories

Model	Description	Picture
ADT110-875-L-INSERT-A	Insert A, ADT875, Low Temp	
ADT110-875-L-INSERT-B	Insert B, ADT875, Low Temp	
ADT110-875-L-INSERT-C	Insert C, ADT875, Low Temp	
ADT110-875-L-INSERT-D	Insert D, ADT875, Low Temp	
ADT110-875-L-INSERT-Z	Insert Z, Blank, ADT875, Low Temp	
ADT110-875-H-INSERT-A	Insert A, ADT875, High Temp	
ADT110-875-H-INSERT-B	Insert B, ADT875, High Temp	
ADT110-875-H-INSERT-C	Insert C, ADT875, High Temp	
ADT110-875-H-INSERT-D	Insert D, ADT875, High Temp	
ADT110-875-H-INSERT-Z	Insert Z, Blank, ADT875, High Temp	
99XX-87X	Carry case for ADT875 with wheels	
AM1710-12-ADT	Secondary PRT, -40 °C to 160°C, 1/4 in dia x 12 in length (6.35 mm X 305 mm), with dry well connector	
AM1710-BEND-ADT	Secondary PRT, -40 °C to 160°C, 1/4 in dia x 12 in length (6.35 mm X 305 mm) , 90° bend at 6.7 in (170 mm) from probe end, with dry well connector	
AM1730-12-ADT	Secondary PRT, -40 °C to 420°C, 1/4 in dia x 12 in length (6.35 mm X 305 mm), with dry well connector	
AM1730-BEND-ADT	Secondary PRT, -40 °C to 420°C, 1/4 in dia x 12 in length (6.35 mm X 305 mm) , 90° bend at 9.6 in (245 mm) from probe end, with dry well connector	
AM1751-12-ADT	Secondary PRT, -40 °C to 661°C, 1/4 in dia x 12 in length (6.35 mm X 305 mm), with dry well connector	
AM1751-BEND-ADT	Secondary PRT, -40 °C to 661°C, 1/4 in dia x 12 in length (6.35 mm X 305 mm) , 90° bend at 9.6 in (245 mm) from probe end, with dry well connector	